

TRUCK MOUNTED MOBILE CONCRETE PUMP

The mobile truck-mounted concrete pump is designed to convey concrete from the machine’s delivery hopper to a point designated by the hirer/site management. This is achieved via a hydraulically powered pump, through pipe sections attached upon an articulated boom, to a suspended flexible rubber delivery hose, solid ‘tremmie’ pipe, or via a steel pipeline laid on the ground or fixed vertically.

Data Sheets detailing pump dimensions, outrigger loadings/ positioning, boom type/ reach, and pumping delivery pressures/ volume outputs are available upon request from POCHIN Concrete Pumping, or via the POCHIN website – www.pochinconcretepumping.co.uk

Information, Instruction, Training, Monitoring - All POCHIN Concrete Pump Operators (CPO’s) are issued with a detailed Operators Procedure Guide (OPG). Every CPO holds a current CPCS card for concrete pumping operations and have attained, or are working towards, NVQ Level 2 qualification. CPO’s are assessed periodically, and are also subject to unannounced ‘spot checks’, in order to ensure safety, quality, & operating standards are maintained and developed.

British Standard BS 8476:2007 ‘Code of practice for the safe use of concrete pumps’ is recommended to hirers and interested parties as a reference document detailing the general minimum requirements in respect of the operation of concrete pumping equipment. Copies of the standard are available from BSI – www.bsi-global.com

Safe Systems of Work – POCHIN Concrete Pumping have assessed all aspects of its operations, and have developed procedures and safe systems of work that aim to reduce and control risks to safety, health, and the environment.

Significant Risks As an overview, the significant risks that are present in respect of concrete pumping activities are noted below, along with appropriate control measures.

Risk	Pochin Control	Site Management and Hirer Considerations & Controls
collapse or settlement of pump due to ground conditions/ inadequate ground bearing	sole plates are provided for placement below outrigger feet to support the pumps outriggers/ reduce surface damage these are designed for use on firm, level standing	ensure ground conditions at set-up position are adequate for imposed load of pump provide sufficient extra support (timbers, steel sheets, etc.) as required
overturning of pump/ collapse of boom due to insufficient stability	the CPO shall ensure that outriggers are extended to the appropriate position	ensure adequate space is available for the pump, and for the full deployment of its outriggers
collapse of placing boom due to failure of hydraulics	all hydraulic rams are fitted with lock valves to limit movement should failure occur	-
structural failure of pump/ boom, or part thereof	all pumps undergo an annual thorough examination (which is certificated), and are also inspected as part of the regular servicing schedule	-
vehicle movements (reversing) - crushing or trapping of persons when moving pump to work position on site	all POCHIN mobile concrete pumps are fitted with a warning ‘bleeper’ which is activated when reverse gear is selected. POCHIN mobile concrete pumps are fitted with appropriate visibility aids (mirrors, CCTV) subject to age/ vehicle size	provide a competent person to act as a banksman during reverse movements limit access for persons to area of vehicle movement

TRUCK MOUNTED MOBILE CONCRETE PUMP

Risk	Pochin Control	Site Management and Hirer Considerations & Controls
vehicle movements (reversing) - crushing/ trapping of persons by visiting concrete mixer trucks	where possible, the CPO will direct the mixer truck during the reversing manoeuvre onto the concrete pump	provide a competent banksman to direct concrete mixers trucks (especially when the CPO is required to operate the boom/ pump at a distance from the machine)
contact with overhead electricity cables	POCHIN Concrete Pumping follow industry guidance (GS6), which specifies that the minimum safe working distance from electric cables, is 6 metres. This includes the fully extended boom radius. <i>(Exceptions may apply , and closer distances may be permitted where engineered controls are provided, however these must be managed by a written safe system of work)</i>	ensure that the proposed pump set up location is such that neither the pump nor the boom can make contact with overhead cables. where set-up location cannot be clear of overhead cables, consideration should be given to the provision of a ground level pipeline to convey the concrete
crush or impact by boom, or struck by placing hose, during initial or subsequent positioning, or during 'off the boom' placement of concrete	every pump is provided with a remote control unit (RCU) allowing the CPO to operate the pump/ boom from a position of safety/ improved visibility the CPO shall visually monitor the unfolding/ folding, and positioning of the boom, and ensure no person is placed at risk by any movements the CPO shall ensure that during movement to position, the placing hose is not allowed to swing in the vicinity of any person	provide sufficient set-up space, and height for unfolding/ folding/ moving the boom ensure persons remain clear during boom and hose movements operatives controlling the position of the placing hose should hold it at arms length person(s) shall be nominated to converse with and signal the CPO, for minor boom positioning during concrete placement ensure adequate luminance and visibility is available where the boom has to be unfolded/ folded/ moved during the hours of darkness or in low light environments.
contact with moving pump components	all moving components upon the concrete pump are fully guarded either by virtue of its manufacture, by mechanical guard, or by automatic interlock systems	ensure operator has carried out his required daily and weekly checks (via our company CP1 form) ensure all machinery examination certificates are checked on arrival to site
injury to persons in vicinity of pumping operation	the CPO shall follow the requirements as stated in the POCHIN Concrete Pumping OPG, safe systems of work documentation, and 'local' site rules as advised during induction	ensure operators are trained and qualified to operate the necessary category of plant (e.g. CPCS/NVQ held by operator) ensure <u>ALL</u> concrete laying personnel and other persons working in the vicinity are briefed <u>prior</u> to the pour, on all risks involved with the pumping operations. The briefing should be acknowledged and recorded. -demarcate area of pump operation limit access to persons, especially below boom, or in vicinity of pipeline or placing hose

TRUCK MOUNTED MOBILE CONCRETE PUMP

Risk	Pochin Control	Site Management and Hirer Considerations & Controls
# potential blockages at start or restart of the pump – use of suspended hose ‘off the boom’.	<p>only ‘single ended’ hoses shall be used – double/ steel collared hoses shall NOT be used ‘off the boom’</p> <p>the CPO shall request that all persons remain clear of the suspended hose at each start or restart of the pump.</p> <p>persons shall only be permitted to approach the suspended hose once ‘smooth flow’ has been achieved</p>	<p>ensure ALL persons shall remain clear of the hose at EVERY start or restart of the pump.</p> <p>‘Clear’ means a safe position at a radial distance of at least twice the length of the suspended delivery hose – referred to as the ‘Danger Zone’</p>
# bursting of pipelines/ hoses under pressure	<p>only pipes, hoses, clips, of sufficient safety rating shall be used</p> <p>wear and damage shall be monitored by the CPO, and checked during scheduled services.</p> <p>excessively damaged/ worn components shall be withdrawn.</p>	-
# - For blockage RISK REDUCTION and CONTROL MEASURES, see page 4		
forceful ejection of air/ concrete from end of pipeline - air sucked into line and compressed	<p>pipe jointing seals shall be clean and in good order</p> <p>concrete level in the pumps hopper must be maintained at the required level– newer pumps have level sensors as standard</p>	(where the CPO is required to position himself remote from the pump) appoint a competent person to monitor deliveries and hopper concrete level (to ensure air is not pumped into the pipe system)
pressurised concrete release - dismantling of a pipeline	the CPO shall ensure that the pipeline is de-pressurised before freeing any jointing clips	employees of the hirer must NOT uncouple pipes without express permission of the CPO
pipeline cleaning with compressed air - pressurised release/ ejection of sponge ball/ concrete/ water/ air	<p>the CPO has a specific written procedure for this operation</p> <p>other personnel shall only be involved under his strict direction</p>	a demarcated and access restricted area shall be provided at the end of the pipeline that is to be air cleansed
working at height (upon the pump deck)	<p>access shall be restricted to ‘short duration’ only (e.g. to retrieve a required component, fill the water box, etc)</p> <p>for longer duration tasks (e.g. to change a pipe seal, etc.), the use of a harness and restraint lanyard(s) shall be required</p>	no hirer personnel, or other non POCHIN employee shall be permitted to access the pump deck, unless express permission is given by the CPO
harmful substances - health effects or personal injury	all substances used as part of the pumping process have been COSHH assessed, and briefing provided to those affected (cement/ concrete, grout products, fuels, oils, greases, etc)	-
environmental impact - spillage of fuel/ oils - inappropriate wash out facility	<p>a kit is provided in all pumps, to contain/absorb fuel/oil spillage</p> <p>the CPO shall only wash out in areas defined and authorised by site management</p>	- hirer/ site management shall provide adequate wash out facilities for concrete residues, etc.

TRUCK MOUNTED MOBILE CONCRETE PUMP

Blockages - why do they occur?	Risk Reduction/ Control - (P) = POCHIN, (H) = Hirer (SM) = Site Management
segregation of the concrete/ aggregates as it is pushed through the pipeline with the primer/ grout	it shall be ensured that the appropriate grout mix is used (P) maximum pipeline and delivery hose length shall be considered - grouting may be more successful in shorter sections (P), (H)
inappropriate concrete mix design or consistency – not suitable for pumping	only concrete that is of 'pump mix design' and appropriate quality should be specified for delivery to the pump (H) or (SM).
stiffening of the concrete in boom/ pipeline from standing for too long (usually when awaiting delivery of fresh concrete) - water bleeds from concrete/ aggregates separate - incorrect dosage of plasticiser (flash set)	for 'standing concrete' the CPO shall circulate or 'move' the concrete in the hopper/ boom/ pipeline (P) deliveries shall be time managed and planned appropriately (H) or (SM)
the flexible placing hose has become kinked, restricting concrete flow	the flexible delivery hose must never be kinked – it should be suspended vertically when used 'off the boom', or kept 'straight' if used at the end of pipelines (H)
'foreign objects' delivered from visiting mixer drums	the quality of the delivered concrete shall be monitored (P), (H) and (SM)
<p>NOTE: Where the concrete condition is believed to be of poor or un-pumpable quality, or where fresh concrete has not arrived in time, and concrete in the boom/ pipeline is becoming too stiff, the CPO may have to reject the load, or clear the concrete from the pump. The hirer shall be informed of this should it be likely to occur.</p>	
<p>Blockages – reacting to</p>	
<p>Where possible, the CPO will stop the pump action <i>and</i> reverse the pumping direction (this may free the blockage). Before the CPO restarts the pumping action, he should ensure all persons retreat to a safe distance away from the boom/ pipeline.</p>	
<p>Should the blockage persist, the CPO will stop the pump, depressurise the line, and investigate the location of the blockage before taking appropriate action (i.e. disconnecting pipe work to locate and remove the blockage).</p>	
<p>A momentary blockage may occur that frees immediately this is often accompanied by increased engine/ pump revs, and noise. The CPO shall endeavour <i>where possible</i> to warn persons in the vicinity to stand clear. However, the release is likely to cause the delivery hose and/ or boom to move or 'kick', before the pump action can be stopped.</p>	

Further Information

The above information has been provided to assist hirers, customers, and site management in identifying and controlling the significant risks associated with concrete pumping operations.

Where any doubt remains in respect of acceptable operational or safety, health, or environmental standards, clarification may be sought at the time of order/ hire, or directly from POCHIN SAFETY DEPT – 01606 831 587